

## **DX273**EDUCATION PROJECTORS



# Versatile Portable Projector with High Brightness



### **FEATURES**

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 4000 Lumens of brightness and 20,000:1 contrast ratio for clear, crisp and bright presentations
- XGA (1024 x 768) native resolution scalable up to a maximum WUXGA (1920 x 1200) resolution
- Dual-HDMI inputs for high definition content with the same high quality
- Compact and lightweight at 2.6kg for easy portability
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- Audio ready with built-in 2 watt audio speaker, audio-in and audio-out ports









#### From meeting room to presentations anywhere on the road

The DX273 is a native XGA digital projector from Vivitek. It features  $\mathsf{DLP} \+ \! \mathbb{R}$  and  $\mathsf{BrilliantColor}^{\text{\tiny{TM}}}$  technologies to display distinct, vibrant images in a widescreen format. The Vivitek DX273 features numerous connectivity options including two HDMI v1.4, a brightness level of 4000 Lumens and a 20,000:1 contrast ratio. With its light weight and compact form, the DX273 projector is easy to install and will fit into any budget.



#### **DX273 SPECIFICATIONS**

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	4000 ANSI Lumens
	Native Resolution	XGA (1024 x 768)
	Max. Supported Resolution	WUXGA (1920 x1200) @60Hz
	Contrast Ratio	20,000:1
	Native Aspect Ratio	4:3
	Keystone Correction	Vertical: +/-40°
Optical	Throw Ratio	1.94 - 2.33 : 1
	Image Size (Diagonal)	40" - 300"
	Projection Distance	1.6 - 12.2 m
	Projection Lens	F = 2.42 - 2.62, f = 22.5 - 25.79 mm
	Zoom Ratio	1.2x
	Offset	106%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI Number of Ports 1.4b (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RS-232, USB miniB (Service)
General	Lamp Life and Type	5,500 / 7,000 / 10,000 Hours (Normal / Eco. / Dynamic Eco. Mode), 210W
	Speakers	2 W
	Dimensions (W x D x H)	331 x 244 x 105 mm
	Weight	2.6 kg
	Noise Level	32dB / 29dB (Normal / Eco. Mode)
	Power	Supply: AC 100-240V, 50/60Hz Consumption: 210W (Eco. Mode), 250W (Normal Mode), <0.5W (Standby)
	Warranty	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whichever comes first, Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region) Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (XX5810005600 ), Remote Control P/N (XX5040005400),